

**NISE 52-SERIES****TECHNICAL DATA**

Front



Rear



Apollo Lake

Model	NISE 52
Article n°	165244

**SYSTEM**

CPU	Intel® Celeron® J3455 QC 1,50 GHz
Chipset	SoC
RAM	8 GB DDR3L SO-DIMM (max 8 GB)
HDD /SSD	128 GB SATA-6G mSATA
mSATA / CF / SIM Slot	1 x nano SIM-card slot

**I/O INTERFACES**

Graphics	3 x HDMI
Serial Ports	3 x RS-232, 1x RS-232/422/485 with Autoflow Control
USB	6 x USB3.0 2 x USB 2.0
Ethernet	3 x Intel® I210 Gigabit-LAN
Audio	Line-out
Other	4x GPI, 4x GPO
Expansion slots	–
Additional extensions	2 x Mini-PCIe for optional WLAN / BT / 4G LTE & mSATA Modules 1 x Antenna hole

**FURTHER DATA**

Operating system	Microsoft® Windows® 10 IoT Enterprise
Operating temperature	0°C to +45°C with ambient airflow according to IEC60068-2-1; IEC60068-2-2; IEC60068-2-14
Relative humidity, non-condensing	10% to 90%
Power	24 V, 60 W Power Adapter
Dimensions (w x h x d)	162 x 26 x 150 mm
Packing list	quick installation guide, driver CD, Windows® Recovery Medium, power adapter, 2 x rail kit